

5           **SYSTEM AND METHOD FOR MANAGING AND DISTRIBUTING ASSOCIATED  
              ASSETS IN VARIOUS FORMATS**

CROSS-REFERENCE TO RELATED APPLICATIONS

10           This patent application is a continuation-in-part application  
of United States Patent Application Serial No. 09/654,101, filed  
August 31, 2000, the entire contents of which is hereby expressly  
incorporated by reference.

15           FIELD OF THE INVENTION

20           The present invention relates to a central system and  
corresponding method for managing and distributing a collection of  
digital assets. More particularly, the invention relates to a  
system and method that receives a set of digital assets that are  
packaged together in some predetermined manner, and that separates  
the packaged digital assets into individual, discrete assets for  
distribution to, and management by, appropriate destinations.

25           BACKGROUND OF THE INVENTION

Information is collected and presented to people in many  
different ways. Written text, in the form of books, newspapers,  
and magazines, represent one conventional way of presenting readers  
with information. Electronically, the written text, in the form of  
text data, may be presented to people over a computer or other

5 similar device. For example, people may access a web site that provides news and other textual information, along with information in other media formats, such as pictures and other images.

Another way in which information is presented to people is via a presentation, in which a person communicates such information to  
10 a person or group of persons. To assist the presenter in communicating such information, conventionally an overhead projector is used to display a sequence of transparent slides, with each slide typically consisting of text and/or some graphical image. The slides are complemented by the presenter who provides  
15 narration for the respective slides.

With computers gaining in terms of popularity, such presentations are often carried out through the use of a computer running appropriate software. One example of such software is PowerPoint™ available from Microsoft Corporation. As is well known  
20 in the art, PowerPoint™ creates a series of screen slides that typically include written text, and that may include a graphical image or the like. The screens are arranged in some order as dictated by the author. During presentation, the screens are displayed, with the progression from one screen to another being  
25 controlled by the presenter, or alternatively being performed automatically by the software.

While such software provides significant benefits and advantages, there are still disadvantages associated therewith. For example, in a conventional presentation, the author must bring  
30 an electronic copy of the presentation, run PowerPoint™ on a computer, and carry out the presentation. There is no provision for on-demand sharing of the presentation. In addition, typically the presenter and the audience must be in the same physical location. Moreover, the presentation is typically performed live.

5           Thus, it would be desirable to have a system and method that  
allow for hosting a presentation from one central location, such  
that the audience can be at respective discrete locations. In  
addition, it would be desirable to have such a system and method  
that is designed to receive a packaged presentation and to  
10   unpackage and distribute the presentation to various destinations.  
Furthermore, it would be desirable, in one embodiment, to  
distribute the associated assets over a communications network in  
a streaming media format, thereby mitigating the need for the  
recipient to download the entire presentation before beginning to  
15   view it. The present invention addresses one or more of these  
desirable features.

#### SUMMARY OF THE INVENTION

20           The present invention provides a system and method for  
managing and distributing a multi-media presentation from a single,  
central location. In one illustrative embodiment, the system  
utilizes a plurality of servers to manage the appropriate assets of  
the presentation. The system receives a packaged presentation over  
a communications network, where the presentation consists of a  
25   plurality of files in different file formats. The presentation is  
unpackaged by the system, and the individual files are distributed  
to the appropriate servers. In one embodiment, a copy of the  
entire, packaged presentation is also maintained by the central  
system. Then, a requester may access the system and request to  
30   download the presentation, in which case the packaged presentation  
is retrieved and transmitted to the requester. Alternatively, the  
central system may host the presentation, with the respective  
servers cooperating to transmit the various files to the requester  
in a streaming manner.

5           Thus, in one embodiment, the invention is directed to a method  
of managing a set of digital assets transmitted over a  
communications network. According to the method, a set of digital  
assets is received, where the assets are packaged together in a  
predetermined manner. The digital assets are then unpackaged,  
10           resulting in plural discrete assets. For each of the assets, an  
asset type is determined, as is a corresponding destination for  
each asset based on the asset type. The respective assets are then  
distributed to the appropriate destinations.

15           In another embodiment, the invention is directed to a system  
for managing a set of digital assets that are transmitted over a  
communications network in a packaged manner. The system includes  
a first server that is operative to receive the packaged digital  
assets. The system also includes a streaming media server that is  
operative to manage streaming media files, a web server that is  
operative to manage web files, and a database server that is  
operative to maintain associations between the package and the  
20           respective individual assets. The first server is operative to  
unpack the digital assets into discrete assets, determine the  
file types of the respective assets, and to distribute the assets  
to the appropriate servers based on the determined files types.  
25

#### DESCRIPTION OF THE DRAWINGS

Other features and advantages of the invention will become  
apparent from a description of the figures, in which:

30           FIG. 1 is a schematic diagram of a system for creating multi-  
media presentations according to one illustrative embodiment of the  
present invention;

          FIG. 2 is a flow chart depicting the operational flow of the  
system of FIG. 1 during the creation of a presentation;

5           FIG. 3 is a flow chart depicting in detail the exportation of data into a template-based format according to one illustrative embodiment of the invention;

10           FIG. 4 is a flow chart depicting in detail the assembly of a presentation into a single, executable file according to one illustrative embodiment of the invention;

          FIG. 5 is a flow chart depicting the operational flow of an unpackaging process according to one illustrative embodiment of the invention;

15           FIG. 6 is a flow chart depicting the operational flow during playback of a presentation created according to the system of FIG. 1;

          FIG. 7 is a flow chart of an event handling process according to one illustrative embodiment of the invention;

20           FIGS. 8 through 13 are screen shots during creation of a multi-media presentation;

          FIG. 14 is a block diagram of an illustrative embodiment of the invention, in which a central system is provided for managing and distributing assets over a communications network;

25           FIG. 15 is a flow chart showing operation of the system of FIG. 14 in managing assets for subsequent distribution;

          FIG. 16 is a flow chart showing the steps involved in unpackaging a presentation according to one illustrative embodiment of the invention;

30           FIG. 17 is a flow chart showing distribution of the assets associated with a presentation to a requester according to one illustrative embodiment of the invention; and

          FIGS. 18 through 21 are screen shots showing interaction with the central system of FIG. 14 during transfer of assets to the system.

## 5 DETAILED DESCRIPTION OF THE INVENTION

Referring now to FIGS. 1 and 2, there is shown a system 20 for creating multi-media presentations according to one illustrative embodiment of the present invention. System 20 includes a user interface 22 including an input device 23 and display 28, a processor 24, memory 26, and microphone 30. Memory 26 stores suitable software for creating the multi-media presentations, as is described in more detail below.

Input device 23 of user interface 22 may take any suitable form, such as a keyboard, keypad, mouse, any other input device, or any combination thereof. An author may enter text data through user interface 22, or may use the interface to select appropriate graphical information from a disk storage medium or other source, as is described in more detail below.

Processor 24 is connected to user interface 22, and to memory 26. Processor retrieves the presentation-creating software from memory, receives data and control commands from user interface 22, and displays the presentation information on display 28.

The present invention can be configured to be used, independently, by an end-user or, in the alternative, the invention can be integrated, as an add-in, into another presentation development application. In a preferred embodiment, the system of the present invention is designed for use in conjunction with Microsoft PowerPoint™. It will be understood by those skilled in the art that PowerPoint™ is merely one suitable software program into which the present invention may be incorporated.

Referring now to FIG. 2, an illustrative method according to the invention will be described for modifying and preparing an existing presentation that consists of multiple digital assets in the form of screen slides. Operation begins at step 40, with the

5 processor 24 retrieving the presentation-creating software from  
memory 26. At step 42, processor initializes the system 20.  
Preferably, initialization consists of setting microphone 30 as the  
currently selected recording object and setting the recording level  
10 level, such as 50%.

During initialization, processor 24 also preferably resets the  
size of link sound files. Preferably, processor 24 is programmed  
to initialize the linked sound files to a relatively large size.  
In a preferred embodiment, the preset size is 2 megabytes. It will  
15 be understood that the file size could be made to be larger or  
smaller, as necessary.

At step 44, system 20 receives an existing presentation,  
either from an external source, or from memory 26. The  
presentation consists of a plurality of screen slides arranged in  
some predetermined order. In one embodiment, the first screen  
20 slide of the presentation is presented on display 28. At step 46,  
the author selects one of the screen slides, for example, by  
clicking on suitable icons in a tool bar to scroll through the  
screen slides, through a drop-down menu, or in any other suitable  
25 manner.

Once the author has selected a particular screen slide,  
operation proceeds to step 48, and processor 24 receives an audio  
clip to be linked with that screen slide. A suitable icon is  
preferably displayed on the screen to alert the author that they  
30 can begin speaking the desired audio clip, with the microphone 30  
capturing the audio and forwarding the audio data on to processor  
24. Alternatively, the audio clip can be imported from a file,  
disk, or the like.

5           Processor 24 stores the audio data in a suitable temporary  
file. In addition, processor 24 generates a link between the audio  
data and the corresponding screen slide, and stores that link,  
either with the audio clip itself, or in a separate linked file.  
Alternatively, the audio clip can be stored directly with the  
10 screen slide in a slide object, as described in more detail below,  
thereby obviating the need for any file linking.

15           In another embodiment, the author can progress through all of  
the slides sequentially, such as if they were making a live  
presentation, without the need to use the narration capture  
interface. The narration would be captured automatically along  
with the slide advance timings. This embodiment is very useful for  
creating an archive of a live presentation at the time of the live  
presentation and as a by-product of the live presentation.

20           At query block 50, processor 24 determines whether there are  
additional slides for which an author desires to record audio  
clips. In one illustrative embodiment, processor may query the  
author whether they wish to record additional audio clips. If so,  
operator proceeds back to step 46, and the author selects another  
slide. Alternatively, processor 24 can display the screen slides  
25 sequentially, with the author deciding whether to record an audio  
clip for a particular screen slide when that screen slide is  
displayed on display 28.

30           If, on the other hand, there are no more audio clips to be  
recorded, then operation proceeds to step 52, and the author  
selects one or more of the screen slides for assembling into a  
final presentation, along with a desired compression format to be  
employed. Such selection of the slides can be done through a drop-  
down menu, or by scrolling through the various screen slides and  
selecting the desired slides, or in any other suitable manner. The



5 selection of the compression format can be done via a drop-down or other suitable menu.

10 Once the author has finished selecting the slides for assembly, operation proceeds to step 54, and processor 24 generates a playlist object corresponding to the selected slides. The playlist object is an intermediate representation of the metadata, and contains the semantic and relationship information for the content, and is a self-contained entity that consists of both data and procedures to manipulate the data. The playlist object includes a media object to store the audio clips, a screen slide object to store the screen images, and a text object to store the text contained in the various screen slides. The media, text, and screen objects also store timing information that defines the temporal relationships between the respective types of data, as is described in more detail below.

20 Then, at step 56, processor 24 copies the text from the selected screen slides as searchable text data into the text object. The text for each slide may be preceded by an appropriate header or the like so that a link is maintained between the text data and the particular screen slide from which that text data originated. At step 58, the individual audio files from each of the selected screen slides are extracted from the respective slide objects and are concatenated into a single audio file which is stored in the media object. The single audio file is then compressed using the particular compression format previously selected by the author, at step 60. Thus, by allowing the author to select the compression format and then compressing the audio file after concatenating the individual audio clips together, the author may to some extent control the file size and sound quality.

5           Alternatively, instead of "physically" concatenating the audio files together as described above, a new file may be created that maintains plural links to the respective audio files. This is an alternate version of concatenation that may be used in connection with the invention.

10           At step 62, slide timing information from the selected slides is extracted from each slide object, and the information is stored in a suitable file. For example, each screen slide will have timing information relating to the start and stop times that the screen slide is to be displayed, which serves to determine the order in which the screen slides are to be displayed.

15           Then, at step 64, the selected screen slides are saved in a graphics file format, preferably in Graphics Interchange Format ("GIF") format, and stored in the screen slide object. It will be apparent to those skilled in the art that other suitable graphics file formats may also be used.

20           At step 66, processor 24 assembles the selected screen slides, in GIF or some other format, with the corresponding audio files, text files, and the file containing the timing information, to create a single compressed, executable file. The process of forming the single executable file is described in greater detail below in connection with FIG. 4. The executable file may then be forwarded to one or more recipients for subsequent viewing of the presentation. For example, the file can be a Windows® 98 or Windows® NT standard executable file, as is well known to those skilled in the art. As is well known, an executable file is a binary file containing a program in machine language that is ready to be executed when the file is selected. In that manner, the executable file may be opened within a suitable web browser or

5 directly in the operating system interface without the need for the presentation software that was used to create the presentation, as is described in greater detail below in connection with FIG. 3.

10 It will be apparent that the system 20 may be used with appropriate software to create the entire presentation at one time. Thus, rather than retrieving a multi-media presentation, system 20 can present an author with blank templates, into which the desired text and/or graphical data can be entered. Audio clips can then be recorded for one or more of the created slides, either concurrently with the creation of the slide, or after the slides are completed.

15 Referring to FIG. 3, an export process that is used to process data contained in the playlist object is described in detail. The export process is designed to transform the data into a template-defined data format suitable for display within a browser. The export process utilizes a plurality of text templates and slide page templates to arrange the meta data from the playlist object such that it is in a browser-suitable format, so that the presentation can be displayed in a browser without the need for the presentation software used to create the presentation. In addition, executable java scripts and applets are generated and  
20 inserted into the template, and are run in the browser to allow for the presentation to be displayed in the browser.

25 The export process begins at step 70, with processor 24 retrieving the playlist object with the slides and clips in temporal order. At step 72, the export process retrieves a  
30 template from the set of templates. For example, the template may be a text information file that will contain information describing how the meta data from the playlist object needs to be formatted into a format that is suitable for running in the browser. In

5 addition, the template contains information relating to the layout  
of the presentation, for example, the relative locations on the  
display of the slides, table of contents, media player controls,  
search results, and the like. The template also will contain  
formatting information, for example, text font, size, color, and  
10 similar attributes. Moreover, the template also contains  
references to other files that are used in the display of the  
presentation.

At step 74, the export process processes the command  
parameters contained in the template to determine what type of file  
15 it is, and the destination of the completed file. At step 76, the  
export process reads the first tag in the template. The tag serves  
as a text replacement holder. For example, the first tag may  
instruct the export process to process the table of contents  
information, the text information, or the slide page information.  
20 Within the first tag there are a number of subordinate tags (i.e.,  
there is a hierarchy of inner and outer loops of tags). Thus,  
where the first tag corresponds to the table of contents, there  
will be multiple entries to be processed, such as the title of each  
slide. Then, for the first title, there are plural tags in the  
25 template to be replaced with corresponding data from the playlist  
object. For example, the tags may correspond to character font,  
size, spacing, positioning, and the like. Thus, each tag is  
replaced by the corresponding information contained in the playlist  
object. In the case where the template is a text template,  
30 processor 24 retrieves the text-related meta data and inserts that  
information into the template. Likewise, in the case of a slide  
page template, the corresponding meta data relating to the slide is

5 retrieved and inserted into the appropriate location of the template based on the tags in the template.

Thus, at step 78, based on the particular tag read by the export process, corresponding meta data is retrieved from the playlist object and inserted into the template, along with  
10 references to the appropriate files, for example, a slide file or the data file containing the actual text data. At query block 80, the export process determines whether there are additional tags remaining in the template to be replaced with information from the playlist object. If so, operation proceeds back to step 76.

15 On the other hand, if all of the tags have been replaced for a particular template, operation instead proceeds to query block 82, and the export process determines whether there are additional templates to be processed. If so, operation proceeds back to step 72. If not, operation proceeds to step 84, and the export process  
20 searches for .tpl files (i.e., template files). For each .tpl file, the export process creates a new file for each slide and replaces an internal tag with the name of the graphic file. The process then terminates.

Thus, by processing the data using the export process and the  
25 template-defined format, the presentation may be viewed in a conventional web browser. Thus, a recipient of the presentation need not have PowerPoint™ software in order to view the presentation.

Referring now to FIG. 4, the process of packaging the files  
30 into a single, executable file is described in detail. Operation begins at step 90, with processor 24 receiving input from the author regarding packaging information and preferences. For example, the author is prompted to input an output file name, the

5 name of the directory to be packaged (i.e., where the respective  
files are currently stored), a directory name where the unpackaged  
files should be stored, an auto-start file (i.e., the first file to  
be opened when the executable file is selected), and package  
10 identification information to uniquely identify the package and its  
source or origin. At step 92, processor 24 creates and opens an  
output file into which the single file will be stored.

At step 94, executable code is copied to the output file. As  
is well known in the art, the executable code is the code that is  
run when an executable file is selected. The executable code  
15 controls the unpackaging process, as is described in more detail  
below in connection with FIG. 5.

At step 96, in the event that package identification  
information was input by the author, corresponding block  
identification information and package identification information  
20 is written to the output file. The information preferably consists  
of a starting block flag, block identification information, and the  
package identification information itself.

Operation then proceeds to step 98, and the destination  
directory information is stored in the output file, along with a  
starting block flag and block identification information to  
25 identify the contents of the block. Following the identification  
information, a data string (e.g., a 16-bit string) is written to  
the output file, which indicates the length of the directory  
information. And finally, the destination directory information  
30 itself is written to the output file.

Then, at step 100, each file in the directory to be packaged  
is sequentially processed and written to the output file as an  
individual block. As described above, an author will have

5 previously selected a number of the screen slides to be included in  
the presentation. Processor 24 accesses the playlist object and  
retrieves the GIF files for the selected slides from the screen  
slide object, the single concatenated and compressed audio file  
from the media object, and the data file containing the  
10 corresponding text data from the text object. In addition,  
processor 24 retrieves the file containing the timing information  
for the selected slides.

15 At step 100, for each file a starting block flag is written to  
the output file. File identification information is then stored to  
identify the file. Next, the string length of the file name is  
written to the output file, followed by the file name itself.  
Then, processor 24 determines whether the file is compressed: if  
not, the file is compressed and stored in a temporary location.  
Processor 24 next writes information (preferably 32 bits) relating  
20 to the size of the compressed file to the output file. Finally,  
the compressed file is written to the output file, either from the  
temporary location, or from the originating directory. If a  
temporary file was created, it is then deleted.

25 Operation then proceeds to query block 102, and processor 24  
determines whether the unpackaging directory is a temporary file.  
If not, operation proceeds to query block 106. If so, operation  
instead proceeds to step 104, and a clean-up program is retrieved  
by processor 24 to be included in the output file. The clean-up  
program is an executable file upon being expanded, and is operative  
30 to delete the files contained in a particular temporary file. In  
this manner, the expanded files contained within the executable  
file do not permanently occupy memory on the recipient's machine,  
unless the presentation is intended to be permanently saved on the

5 recipient's machine, in which case a destination directory other than the temporary directory is selected.

Storage of the clean-up program is as follows: first, a starting block flag and clean-up program identification information are written to the output file. Then, the clean-up program is  
10 compressed to a temporary location in memory. The length of the compressed program is written to the output file, followed by the copy of the compressed program. The temporary compressed file is then deleted, and operation proceeds to query block 106.

At query block 106, processor 24 determines whether one of the  
15 files in the bundle was designated as an auto-start file. If not, operation terminates at step 110 with the closing of the output file. On the other hand, if one of the files was designated as an auto-start file, then operation instead proceeds to step 108, and starting block flag and auto-start identification information is  
20 written to the output file, followed by a 16-bit string to indicate the length of the auto-start string name, which is followed by the auto-start string itself. Operation then terminates at step 110, and the output file is closed.

In an alternative embodiment, the package process inserts a  
25 source-identifying block into the package, with such block serving to identify the source of the package. In this manner, the unpackaging process described below can verify the source of the package to ensure that the package does not contain any potentially harmful or offensive data.

30 Referring now to FIG. 5, the unpackaging of the packaged presentation is described in more detail. As is described above, a presentation is packaged into a single, executable file. The executable file may then be transferred to one or more recipients



5 in various ways, either as an email attachment over a communications network, on a disk, or in any other suitable manner.

In another embodiment, the executable file is transferred to a host web site, where the file is unpackaged as described below and made available to recipients over the Internet or some other  
 10 communication network. In that situation, the recipient need not unpack the presentation on their desktop; rather, the unpackaged presentation may be streamed to the recipient slide-by-slide on an on-demand basis. This embodiment is described in greater detail below in connection with FIGS. 14 through 21.

15 In the case where the executable file is delivered directly to the recipient, operation begins at step 120, with the recipient selecting the executable file, for example, by double clicking on an appropriate icon on the recipient's display. Once the recipient selects the executable file, operation proceeds to step 122, and  
 20 the executable code in the file automatically runs and scans the data in the output file until it encounters the first starting block flag. Next, the executable code determines the identity of the data contained in the first block, by reviewing the identification information stored in the block during the packaging  
 25 process.

At query block 124, if the block is determined to be the package identification block, then operation proceeds directly to query block 146 to scan the data for the next block in the file. The package identification block is not processed by the executable  
 30 code during the unpackaging process. If the block is determined to not be the package identification block, then operation proceeds to query block 126, and the executable code determines whether the block contains unpackaging directory information. If so, then

5 operation proceeds to step 128, and the executable code reads the  
 information contained in the block to determine the full path name  
 of the output directory and subdirectories in which to store the  
 files expanded during the unpackaging process. The code then  
 creates all of the necessary directories and subdirectories into  
 10 which the expanded files will be stored. Operation then proceeds  
 to query block 130, and the executable code determines whether the  
 directory into which the files will be saved is a temporary  
 directory. If not, operation proceeds to query block 146. If in  
 fact the directory is a temporary directory, then operation  
 15 proceeds to step 132, and a registry entry is created to control  
 the clean-up program to be executed the next time the recipient  
 logs in to their machine. Operation then proceeds to query block  
 146.

If at query block 126 the data block is determined to not be  
 20 a directory information block, then operation proceeds to query  
 block 134, and the executable code determines whether the block is  
 a compressed file block. If it is, then operation proceeds to step  
 136, and the file name for that file is read from the block and  
 concatenated with the destination directory. The executable code  
 25 then determines whether a corresponding subdirectory exists and, if  
 not, the subdirectory is created and opened. The length of the  
 compressed file is determined, and if the data needs to be  
 decompressed, it is decompressed and written to the destination  
 directory. Operation then proceeds to query block 146.

30 If at query block 134 the block is determined to not be a  
 compressed file, then at query block 138 the code determines  
 whether the block contains the clean-up program. If so, operation  
 proceeds to query block 140, and it is then determined whether the

5 clean-up program is needed or not, by checking the machine's  
temporary directory to determine whether a copy of the program is  
already resident on the machine. If so, operation proceeds to  
query block 146. On the other hand, if there is no resident copy  
of the program, operation instead proceeds to step 142, and the  
10 clean-up program is decompressed to an executable file in a  
temporary directory, such as the Windows temporary directory.  
Operation then proceeds to query block 146.

If the block does not contain the clean-up program, then  
operation proceeds to step 144, and the executable code determines  
15 that the block contains the auto-start file information, and the  
code saves the path information of the auto-start file for future  
use. Operation then proceeds to query block 146.

At query block 146, the executable code determines whether  
there are additional blocks to be unpackaged. If so, the code  
20 reads the identification information of the next block at step 148,  
and operation then proceeds back to query block 124 to determine  
the block type.

If at query block 146 it is determined that there are no more  
blocks to be unpackaged, then operation proceeds to query block  
25 150, and the code determines whether there is a file designated as  
the auto-start file, by checking for auto-start path information.  
If there is an auto-start file, then operation proceeds to step  
152, and the corresponding file is opened to begin the  
presentation.

30 Where the packaged presentation is transferred to an ASP host,  
the host is programmed to override the auto-start data and the  
destination directory information. The host preferably includes  
codes that investigate the package identification information to

5 ensure that the executable file was generated by a known, trusted source, and not by some unknown entity that might be transmitting a virus or other undesirable content. Once the identity of the author is verified, the packaged assets are then unpackaged and distributed in a predetermined manner as determined by the host.

10 The host then stores the presentation until a user accesses the host and requests the presentation. The host can then stream the presentation to the user in any suitable, well known manner, as described above, or can transmit the entire packaged presentation to the user. This embodiment is described in more detail below in

15 connection with FIGS. 14 through 21.

Referring now to FIG. 6, playback of the created presentation is described in more detail. Initially, the presentation is obtained by an intended recipient, either on a disk or other storage medium, as an email attachment, or transferred over a

20 computer network, such as over the Internet. Then, at step 200, the recipient opens the file by clicking on a suitable icon representing the presentation, or in any other well-known manner. As described above, when the bundle is extracted by means of the recipient opening the self-executing file, one of the sub-files is

25 designated as the initial file to be opened, as in conventional in self-executing files. In addition, the extracted files are written to the appropriate destinations for subsequent retrieval during the presentation.

At step 202, the presentation is displayed to the recipient,

30 with the slides being sequentially displayed along with any corresponding audio clips for the respective slides. In addition, a table of contents is displayed on the display, and includes the title of each slide in the presentation (FIG. 13). The titles may

5 be selected by the recipient to advance the presentation to the  
corresponding slide. At query block 204, the recipient's machine  
(hereinafter "the machine") determines whether the recipient has  
requested a search for a particular text string within the  
presentation. In one embodiment, such a request is made by  
10 entering the text string in an appropriate box on the screen and  
then clicking on a corresponding button on the screen (see FIG.  
13). If the recipient does not request a search for text, then  
operation proceeds to query block 205, and the machine determines  
whether the recipient has made a selection of one of the slide  
15 titles in the table of contents. If so, the presentation is  
advanced to the selected slide, and that slide is displayed along  
with the corresponding portion of the concatenated audio file, at  
step 206. A time-based index into the concatenated audio file is  
provided, and instructions are transmitted to reposition an audio  
20 player to the appropriate point in the audio file based on the  
time-based relationship between the slide and the audio file.  
Operation then proceeds back to query block 204. If the recipient  
does not select any of the titles in the table of contents, then  
operation instead proceeds to step 207, and the presentation  
25 continues to completion, and operation then terminates.

If, on the other hand, the recipient makes a request for a  
text search, operation proceeds to step 208, and the recipient  
enters their text string, which is received by system 20. At step  
209, the machine accesses the meta data file that was included in  
30 the self-executing file and that contains all of the meta data  
information necessary for playback, including the text that appears  
on the individual slides. At step 210, the machine compares the  
text string with the text contained in the data file. At query

5 block 212, the machine determines whether a match exists. If not, then at step 214 the recipient is notified that there is no match for the entered text string. Operation then proceeds back to step 204, and the recipient may enter another text string to be searched.

10 If there is a match between the text string and the text in the data file, operation proceeds to step 216, and the machine retrieves the appropriate GIF file and determines the corresponding position within the single audio file and presents the screen slide and corresponding portion of the audio file to the recipient.  
 15 There are many well-known ways in which system may determine the appropriate GIF file to retrieve. For example, an association table may be maintained to link the text of each slide with a corresponding GIF file.

20 It will be apparent that a recipient may request that a search be conducted before the presentation begins, during the presentation, or after the presentation is completed.

Once the slide and corresponding portion of the audio file are presented to the recipient, the presentation may be continued, sequentially from the selected slide to the end of the  
 25 presentation, operation may terminate, or operation may proceed back to query block 204 to allow the recipient to search for another text string.

Referring to FIG. 7, the operational flow of event handling software included in one illustrative embodiment of the invention  
 30 is shown in detail. The event handling software controls the navigation through a presentation at the recipient's machine. The software relies on a set of event data that contains all of the information relating to the timing of the presentation. For

5 example, the event data includes information concerning the start and stop times of each slide page, of each of the clips in a clip list, and of each audio clip. In addition, the event data may include information concerning when the presentation should automatically pause or skip to a new position.

10 Operation of the event handling software begins at step 220, and the presentation begins, for example, when the self-executing file is opened. The presentation then begins to be displayed, for example, at the beginning of the presentation. At step 222, the recipient's machine is controlled by the event handling software to  
 15 determine the time of the current position of the presentation. For example, when the presentation is launched from the beginning, the software determines that the time is either at time zero or only a few milliseconds. At step 224, the time is compared with the event data for the respective slides, and the slide whose time is either equal to or less than the determined time is selected and  
 20 displayed in the slide window on the recipient's machine, at step 226.

At step 228, the event handler software calculates a timeout based on the current time of the presentation and the stop time of  
 25 the slide being displayed. At step 230, the event handler sets a clock to fire an event trigger upon reaching the timeout.

At query block 232, the event handler determines whether the event trigger has fired. If so, then operation proceeds to step 234, and the event trigger initiates a polling process to  
 30 repeatedly (e.g., every 200 milliseconds) determine the current position of the presentation. At step 236, the current position is compared with the event data for the respective slides. At step 238, the slide whose time is 1) equal to or 2) less than, and

5       closest in time to, the current time is selected and the slide  
 window is updated with the selected slide. At step 240, the event  
 handler calculates a timeout based on the current time and the stop  
 time of the slide, and resets the clock to fire an event trigger  
 upon reaching the new timeout. Operation then proceeds back to  
 10       query block 232.

15       On the other hand, if at query block 232 it is determined that  
 the event trigger has not yet fired, operation instead proceeds to  
 query block 242, and the event handler determines whether the  
 presentation has been either paused or stopped by the recipient,  
 for example, by clicking on a pause or stop button, or by selecting  
 another slide for presentation. If not, operation loops back to  
 query block 232. If the presentation has been paused or stopped,  
 then operation proceeds to step 244, and the presentation is  
 stopped. Also, the event trigger clock is cleared. Operation then  
 20       proceeds to query block 246, and the event handler determines  
 whether the presentation has been restarted, for example, by the  
 recipient pressing a start button, or repressing the pause button.  
 If the presentation has been restarted, operation proceeds back to  
 step 222 to determine the time of the new position of the  
 25       presentation.

It will be understood that when the recipient selects a new  
 slide for display, the presentation is automatically restarted at  
 step 246, and operation then proceeds back to step 222.

30       The above description of the event handler deals primarily  
 with the screen slides themselves. However, it will be apparent to  
 those skilled in the art that the event handler would perform the  
 same functions for synchronizing the display of textual  
 information, audio clips, and the like.



5 Referring now to FIGS. 8 through 13, there is shown one  
illustrative embodiment of various interface screens generated by  
system 20 to facilitate creation of a multi-media presentation by  
an author. As shown in FIG. 8, system 20 preferably displays each  
10 of the generated screen slides 21 with the accompanying text for  
each. In addition, a user interface window 320 is provided to  
guide an author through the process of creating a multi-media  
presentation. The user interface navigates the author through the  
steps of initializing the system 20, recording narration for the  
15 respective slides 21, previewing a presentation, and packaging the  
final presentation. The user interface 320 includes a Cancel  
button 322, a Back button 324, a Next button 326, and a Finish  
button 328 to allow the author to control navigation through the  
process.

FIG. 9 shows a user interface 330 which may be used by an  
20 author to calibrate the microphone. The calibration of the  
microphone is performed by providing a volume control 332 that can  
be manipulated by the author to adjust the volume of the  
microphone. The range of control spans from 0 to 100%. The screen  
preferably displays the control level at which the microphone is  
25 set in a display window 334. The level can be increased and  
decreased by manipulating a slide bar 335. To test the volume  
level to determine whether it is acceptable, a control panel 336 is  
provided that enables the author to record and then play back a  
test clip to determine if the volume level of the microphone is  
30 acceptable. Control panel 336 preferably has a record button 338,  
play button 340 and stop button 342. To test the microphone, the  
author clicks the record button 338 and speaks into the microphone.  
When the author is finished recording, the stop button 342 is

5 pressed. The author can listen to the recording by clicking the  
play button 340. When the volume level has been set to a desirable  
level, the author can click the NEXT button 326 to continue with  
the creation of a presentation. If, at any time, the author wants  
to return to a previous window to change a setting, the author can  
10 do so by clicking the BACK button 324.

FIG. 10 illustrates a user interface 350 that assists the  
author in narrating a slide. To begin recording on a particular  
slide, RECORD button 352 is clicked. The author can stop the  
recording at anytime by clicking on STOP button 354. The author  
15 can also pause the recording by pressing PAUSE button 356. The  
author can play back the recording by clicking on PLAY button 358  
to ensure that the audio clip is audible and clear. If the content  
is not as desired, the author can override the previous audio clip  
by recording over it. In addition, interface 350 includes Previous  
and Next Slide Buttons 357 and 359, which allow the author to  
20 navigate through the respective slides 21. Thus, the present  
system allows the author to record the slides out of order, giving  
the author greater independence in working on the slides in the  
order desired by the author and, not necessarily, in the order that  
the slides appear in the presentation material.  
25

When finished narrating a slide, the author can proceed to the  
next slide by clicking on NEXT slide button 359, or to a previous  
slide by clicking on PREVIOUS slide button 357. The activation of  
either of those buttons will automatically terminate the narration  
30 for that slide. Thus, it will be apparent that user interface 350  
allows the author to record narration for the respective slides in  
any order. The audio for each slide is independent of the other

5 slides, and thus, the audio for the slides can be recorded in an order independent of the order of the slides.

10 The interface 350 preferably includes a slide time meter 364 that displays the length of the audio for each slide and a total time meter 366 that displays the length of the audio for the entire presentation. This allows the author to keep track of the length of the entire presentation as the author is recording the audio for each slide.

15 In addition to providing information regarding the length of the audio recordings on interface 350, the length of the various audio recordings are also provided as time meter displays 367 under each slide. This enables the author to view the audio recording length for all of the slides simultaneously.

20 In one embodiment, system 20 requires that narration be recorded for each slide, with the length of the recording determining the length of time for which the slide will be displayed. Alternatively, if narration is not recorded for a particular slide or slides, a default display time may be assigned to that slide, such as 4 seconds or some other amount of time. Or, system 20 may query the author to enter a default time for a particular slide for which no narration has been recorded.

25 FIG. 11 shows a user interface 360 that allows an author to preview and/or package a finished presentation. Interface 360 includes a Preview button 362, which if clicked causes system 20 to launch the presentation immediately, so as to allow the author to preview the presentation before completion. The presentation material can be packaged so as to be optimized for sound quality or optimized for size. The author makes their selection by clicking on one of two windows 365 and 367. Clicking on the preview button

5 causes the processor 24 to carry out the concatenating,  
compressing, and export processes so as to have the data in a  
format suitable for presentation within the web browser. In  
addition, the preview function causes the processor to launch the  
10 auto-start file in the web browser automatically, as would be done  
by the unpackaging process described above.

FIG. 12 depicts a user interface 370 to allow the author to  
select a file name under which the presentation will be stored. In  
a preferred embodiment, optimizing the presentation for size  
provides a compression of about 6500 bits per second, whereas  
15 optimizing for sound quality provides a compression of about 8500  
bits per second. In the embodiment shown in FIGS. 9 and 10, the  
user interfaces 360 and 370 only allow the author two choices for  
optimization, namely, optimization for sound quality and  
optimization for size. The system, however, can be adapted to  
20 provide additional optimization choices to the author. For  
instance, if authors desire a different level of audio, e.g., audio  
at a high bandwidth to facilitate high quality CD recording, the  
system can be adapted to provide additional optimization choices to  
the author. The optimization for sound quality and size are  
25 preferable for presentation materials that mainly contain audio  
consisting of the spoken word. In the case of audio containing  
spoken word, the frequency response is small and telephone-like,  
monaural quality is the audio level that is required to be provided  
by the system.

30 User interface 370 assists the author in saving the  
presentation material. In one illustrative embodiment, system 20  
keeps track of the last used directory 374 and displays the  
directory name in the "save file as" window 372. That directory is

5 concatenated with the current name 376 of the presentation material  
to create the file name for the presentation. For instance, user  
interface 370 displays a directory of "D:\MyDocuments\" and a file  
name of "testing of hotfoot.exe." The presentation material is  
10 thus saved in the specified directory under the specified file  
name. User interface also includes a Browse button 378 to allow an  
author to select another path in which to store the presentation.  
In yet another embodiment, system 20 inserts a default directory  
into window 372, rather than the last-used directory.

15 As is described above, the creation of the playlist object  
allows the system of the present invention to be compatible with  
numerous other applications because the playlist object simplifies,  
generalizes, and abstracts the process of data storage, post-  
processing, and transmission. Thus, the playlist can be reused in  
other applications, while the playlist ensures the referential  
20 integrity, provides object modeling, provides consistency between  
what is done in the present system with other applications, which  
allows efficient and compatible data sharing between different  
applications.

25 The system loops through each slide, extracts the text of the  
slide, and removes the megaphone object from each slide and exports  
it as a .gif file. The exportation of the slide object as a .gif  
file can be done by using Microsoft PowerPoint™. Auto-numbering  
is automatically turned off by the system so as not to get a "1" at  
the bottom of each page. The duration of the audio file for each  
30 file is measured and, if the slide has no audio duration, a  
duration of four seconds is assigned. The reason for assigning a  
four second duration is that the recipient's application is  
responsible for advancing the slides. If there is no audio

5 recorded for the slide, the slide will be shown for four seconds and then is automatically advanced to the next slide.

10 The corresponding audio clips for the selected slides are also retrieved and saved as .wav files. The .wav files are concatenated and integrated together. The .wav files can also be converted to other digital media continuous stream formats, such as MP3. It will be apparent to those skilled in the art that by concatenating the files together, prior to encoding into another digital sound format, the notion of independent audio linked to slides is transformed into a coherent and unchangeable presentation format.

15 The coherent format allows the recipient to jump from slide to slide randomly and out of order but does not allow the recipient to modify or change the audio or the slides. Therefore, the intention of the publisher is preserved.

20 In one illustrative embodiment, the .wav file is converted to a Windows Media file and the bit rate is set to the bit rate previously determined by choosing optimization for size or sound quality. The Windows Media file is a single media file that can be attached to the playlist object.

25 The author has the option of choosing which slides will be included in the presentation package, with such selections being done in any suitable manner, such as by clicking on a window next to each slide, through a drop-down menu, or in any other suitable manner. For instance, the author can chose slides 1, 3 and 7 and those become packaged in the presentation. Or the author can

30 unselect 3 and select another slide, for instance slide 8. The fact that the audio is tied to a slide, as opposed to across the entire presentation, allows the author to chose the order and the slides to be included in the presentation. System 20 extracts the

5 necessary information from the selected slides only when packaging the presentation.

10 The packaged presentation is then subjected to the above-described export process, in which the necessary information is extracted from the playlist object and put into a template-defined format suitable for display within a browser. In one embodiment, system 20 stores the title of each slide in a suitable file for creating the table of contents, and strips all of the text from each slide and stores the text in another file, as is described above. The information proceeds to the packaging process which, as described in detail above, takes the files and subdirectories, including the media file and the slides, and creates an executable file.

15 The packaging process gathers a relatively large number of files, for example as many as 30 to 40 individual files, that are created by system 20 when a slide presentation is created. There may also be other files, such as external files, that also need to be included in a presentation. The packaging process gathers the external files along with the presentation files and creates a single, simplified package. In a preferred embodiment, the packaging and unpackaging functions are completed without interfacing with the author. One of the files in the package is designated as the file to be opened when the package is extracted. A marker is also placed in the executable file that identifies the file as one that is compatible with the application of the present system.

30 Referring now to FIG. 13, there is shown a portion of the presentation, for example when an author has selected the Preview option. The presentation includes a table of contents 400 that

5 includes the title for each of the slides. Each title may be  
 clicked on to immediately display the corresponding slide. In  
 addition, the presentation displays one of the slides 21.  
 Moreover, the presentation includes a window 402 into which the  
 recipient may enter a text string to be searched for. A Search  
 10 button 404 is provided and may be selected by the recipient to  
 begin a search for text, as is described above in more detail. The  
 search results are displayed in a portion of the screen 406. In  
 one embodiment, if there is a match, the slide that contains the  
 matched text is automatically retrieved and displayed, along with  
 15 the corresponding audio clip. Alternatively, the results may be  
 displayed for the recipient, with the recipient then selecting one  
 of the slides for display. The display preferably also includes a  
 Play button 408, Pause button 410, and running indicator bar 412 to  
 indicate the current state of the presentation.

20 Referring now to FIGS. 14 through 21, there is shown another  
 illustrative embodiment of the present invention, in which a  
 central host 500 is provided to manage and distribute one or more  
 presentations. Referring primarily to FIG. 14, the central host  
 500 in one illustrative embodiment comprises a firewall 502, an  
 25 interface (or ASP) server 504, a web server 505, a database server  
 506 (also referred to herein as an "SQL server"), at least one  
 media server 508, and a mail server 510. Firewall 502 preferably  
 comprises a well-known system that is designed to prevent  
 unauthorized access to the host 500 by unauthorized users.  
 30 Firewall 502 can be implemented in hardware, software, or a  
 combination of both. For example, the firewall in one embodiment  
 may comprise a dedicated computer equipped with well-known security



5 measures, or the firewall may be software-based protection, or some combination of the two.

10 The interface server 504 is designated as the server to interface with users accessing the host 500 from respective user terminals 512 (hereinafter referred to as "clients"). Thus, interface server 504 generates the front end that is presented to each client 512, as is described in greater detail below. In addition, interface server 504 manages various other client interactions, including account and presentation management, user authentication (through passwords or other information), billing functions, and the like, all of which is well understood in the art.

15 The web server 505 is designed to manage web page data, graphics, and other such images, including HTML files, Java-script files, image files, and the like, that are included in various presentations received by host 500. While only one web server 505 is shown in FIG. 14, it will be apparent to those skilled in the art that system 500 may include a plurality of web servers 505 along with the appropriate load balancing equipment to efficiently distribute high loads between the respective web servers 505.

20 Interface server 504, in conjunction with SQL server 506, is responsible for carrying out log-in procedures, and for providing account information to respective clients 512, as is described in more detail below.

25 Interface server 504 is also responsible for receiving packaged presentations from a client 512, unpackaging the presentations into discrete asset files, authenticating the presentation (i.e., determining whether the presentation is a valid package type), determining the appropriate destinations for each

5 asset file, and distributing the asset files to the appropriate destinations, all of which is described in more detail below. In one embodiment, server 504 is an active server, for example an Active Server Pages (ASP) server. The interface server 504 may also perform additional functions, such as virus scanning, activity  
10 logging, automatic notification, and the like.

Database (or SQL) server 506 is, in one illustrative embodiment, a database management system that provides database management services for host 500, and stores client identification and verification information, utilization, logging, and reporting information, along with information to identify and interrelate the various files of the respective presentations. As described above, interface server 504 communicates with SQL server 506 to request client account information, as well as information regarding the various asset files, as is described in more detail below.  
15 Moreover, server 506 also maintains conventional billing and accounting information regarding the various users of host 500.

As shown in FIG. 14, host 500 includes at least one media server 508 that is operative to manage and distribute streaming media files. For example, media server 508 may comprise a Windows®  
25 media server, a RealServer® from RealNetworks®, or the like. Preferably, host 500 includes a plurality of different media servers to accommodate various streaming media formats, and may include more than one of each type of server to address scalability issues. The media server(s) receive streaming media files from interface server 504 and maintain the streaming media files until  
30 they are again requested by server 504.

Mail server 510 functions as a mail hub, and in one embodiment is a computer that is used to store and/or forward electronic mail.

5 Relevant message data is generated by server 504 and transmitted to  
mail server 510, which then generates and transmits corresponding  
electronic mail messages to desired recipients. Mail server 510  
also provides file transfer protocol (FTP) services, which allows  
for transferring files from host 500 to a client 512 via a suitable  
10 network, such as the Internet 514.

While in one illustrative embodiment host 500 includes mail  
server 510 to generate and transmit email messages, it will be  
understood that various other forms of electronic messaging may be  
utilized. Thus, email messaging is but one example of messaging  
that may be employed by host 500.  
15

It will be understood by those skilled in the art that  
additional server functions can be provided by host 500, either  
included in one or more of the servers 504, 505, 506, 508, or 510,  
or in additional servers. For example, host 500 may provide the  
necessary functionality to support Internet relay chat, video  
20 conferencing, threaded discussions, tests, surveys, and  
assessments.

As shown in FIG. 14, in one embodiment host 500 and clients  
512 communicate over the Internet 514. It will be understood that  
host 500 and clients 512 may alternatively communicate over any  
other suitable communication network, such as a local area network  
(LAN), wide area network (WAN), over a wireless network, or any  
25 other network that provides two-way communication.

Referring now to FIG. 15, operation of host 500 in processing  
a group of packaged assets is described in more detail. Operation  
begins at step 600, with a user at one of the clients 512 accessing  
host 500 over the Internet 514 or other network. As described  
above, client 512 communicates with server 504 through firewall  
30

5 502. Server 504 presents a log-in screen to client 512 (FIG. 18),  
 and the user at client 512 then transmits a user name and password  
 to server 504. Server 504 accesses database (or SQL) server 506 to  
 verify the received information, for example, by accessing an  
 association table or other data in the server's database. Then, at  
 10 query block 602, server 504 determines whether the client 512 is a  
 registered user. If not, access is denied at step 604. Server 504  
 may then conduct a registration procedure to register the user as  
 a new user. Alternatively, operation may return to step 602, with  
 the user being prompted to re-enter their user information.

15 On the other hand, if at block 602 it is determined that the  
 user provided a valid user name and matching password, then server  
 504 verifies that the user at client 512 is a valid user, and  
 operation proceeds to step 606 where server 504 retrieves  
 corresponding account information from SQL server 506 and presents  
 20 such information to client 512, for example in the form of a  
 suitable display screen (FIG. 19). Operation then proceeds to  
 query block 608, and server 504 determines whether the user at  
 client 512 desires to transfer one or more presentations to host  
 500, for example, by clicking on a suitable icon 609 on the screen,  
 25 or entering the name of a presentation in a suitable window 611  
 (FIG. 19). If the user does not wish to transfer one or more  
 presentations, then operation proceeds to step 610, and client 512  
 and server 504 may engage in other functions, such as generating e-  
 mail messages, viewing existing presentations, deleting  
 30 presentations, associating a password or other authentication  
 information with the presentation, and the like, as is described in  
 more detail below.

5           If the user does wish to transfer one or more presentations to  
 host 500, then operation proceeds to step 612, and the packaged  
 assets are received by server 504, along with source identification  
 data or some other verifiable identifier (hereinafter  
 "identifier"). Preferably, the identifier is generated by the  
 10 client 512 during packaging of the assets, and serves to identify  
 the source of the packaged assets. Alternatively, the identifier  
 may serve to not only identify the source of the assets, but may  
 also serve to identify the type of package being received, which  
 may dictate the functions of host 500 in processing the package.

15           At step 612, server 504 also verifies the identifier, for  
 example, by accessing SQL server 506 and retrieving a corresponding  
 look-up table. At query block 614, server 504 determines whether  
 the identifier constitutes a match. If not, then the source of the  
 packaged assets cannot be verified, and operation proceeds to step  
 20 616, where the packaged assets are discarded.

25           If the identifier included with the packaged assets matches  
 with the identifier data maintained by host 500, then the assets  
 are unpackaged into discrete files and distributed to the  
 respective servers. The unpackaging process is described in more  
 detail above in connection with FIG. 5, and the distribution  
 procedure is described in more detail below in connection with FIG.  
 16.

30           Referring now to FIG. 16, operation of host 500 in processing  
 a received presentation is described in more detail. At step 700,  
 interface server 504 receives the packaged assets from client 512  
 over the Internet 514. As described above, the packaged assets in  
 one embodiment consist of a single, self-executing file (.exe).  
 Alternatively, the digital assets may be packaged together in some

5 other form of single file, in two or more files, or in some other manner.

Operation then proceeds to step 702, and server 504 unpackages the assets into individual, discrete files. Server 504 may use an unpackaging routine similar to the one described above in  
10 connection with FIG. 5, or some other suitable unpackaging procedure.

Then, at step 704, server 504 generates a unique ID and path for the received presentation, with the ID and path being used to identify all of the assets that are associated with the presentation. In one illustrative embodiment, the ID and path is used to create a directory name for the respective files of the presentation. The ID and path may consist of a random string of alphanumeric characters, or any other suitable, unique handle. While in the illustrative embodiment the ID and path is used to  
15 create a directory to store the assets, it will be understood that the ID and path can be used in many other ways to associate the discrete assets of the presentation.

At step 706, server 504 processes one of the asset files, and determines the file extension for that file. Based on the file extension, server 504 determines the appropriate destination for  
25 that file. For example, a file extension of .jpg or .gif would indicate a file that should reside with the web server 505, while a file extension of .rm, .wmv, .asf, and the like would indicate a file that should be distributed to a corresponding one of the media server(s) 508. Such a determination can be made by referring to an association table or the like maintained by host 500.  
30

At step 708, server 504 distributes the asset files to the appropriate server as determined at step 706. Server 504 also

5 creates a directory at the destination server using the unique ID. The file is then stored in a hierarchical manner in the newly created directory. For example, the file name under which the file is stored at the server may be a concatenation of the identifier and the name of that particular file. Alternatively, as described  
 10 above, the asset files may be stored in some other manner at the respective servers, using the file name to associate the various asset files.

Operation then proceeds to query block 710, and server 504 determines whether there are one or more files remaining that must be distributed. If so, operation proceeds back to step 706, and the above-described process is repeated for another asset file.  
 15

If, on the other hand, all files have been distributed, then operation instead proceeds to step 712, and server 504 transmits the unique identifier and corresponding file name information to SQL server 506. SQL server 506 then stores that information in memory (e.g., a database), and links the unique identifier data to the particular presentation in an association table or the like.  
 20

Preferably, server 504 stores a copy of the packaged presentation prior to unpackaging the received presentation. This then allows a recipient at a client 512 to access host 500 and request the packaged (or original) presentation, which as described above is preferably a self-executing file that can be subsequently viewed at client 512 using a conventional browser, without the necessity for remaining in communication with host 500.  
 25

Referring now to FIG. 17, operation of host 500 in presenting a presentation to a recipient is described in more detail. Operation begins at step 800, with host 500 generating and presenting a message to one or more recipients. In one embodiment,  
 30

5 interface server 504 and mail server 510 cooperate to transmit electronic mail messages to one or more recipients. Server 504 may receive a list of email addresses from a registered user (FIG. 20), along with a corresponding presentation that has been transferred by the user to host 500 via client 512. Server 504 then composes  
 10 respective email messages, including a URL to the presentation, and the email messages are transmitted to mail server 510, which is responsible for forwarding the email messages to the recipients.

15 While in one illustrative embodiment, the information containing a link to a presentation is included in an email message generated by host 500, it will be apparent that the information can be delivered and/or made available to recipients in various ways. For example, host 500 may maintain a homepage for each subscriber, with links to one or more of that subscriber's presentations. Each subscriber may then specify whether to make their presentation(s)  
 20 available on their homepage. Users may access a subscriber's homepage and select one of the available presentations. Alternatively, each subscriber may generate their own email messages with a URL to the presentation. It will be understood by those skilled in the art that the location of a presentation may be  
 25 communicated to recipients in many different ways.

At step 802, one of the recipients that receives the email message then clicks on the URL in the email (or alternatively, browses to the homepage and clicks on a URL or image or text that represents the presentation), and is connected with host 500 over  
 30 the Internet 514 or other suitable communication network. Server 504 determines that the recipient is desirous of gaining access to a particular presentation, based on the URL used to link to host 500. Then, at query block 804, server 504 accesses the database



5 maintained by SQL server 506 to determine whether the desired presentation requires viewer authentication, for example, a password or other data. If so, operation proceeds to step 806, and server 504 requests authentication from the recipient (FIG. 21). The recipient provides authentication (password or other  
 10 information) at step 808, and at step 810 server 504 compares the provided information with the corresponding information stored in the database of server 506. If there is no match, then at step 812 access is denied to the recipient. The recipient may then be asked to provide the correct authentication information, or host 500 may  
 15 terminate communication with the recipient.

If the information entered by the recipient corresponds to that stored by database server 506, or if the presentation does not require viewer authentication, operation proceeds to query block 814, and the recipient is presented with a number of options- they  
 20 may either download the packaged presentation for subsequent viewing, or host 500 may present the presentation to the recipient. While the password and selection steps are described as occurring sequentially, the recipient may, in one step, enter a password and select the desired method of transferring the presentation, for  
 25 example by entering the password in a window 815 and then clicking on an icon 817 or 819 that corresponds to the desired method of transfer (FIG. 21).

If the recipient wishes to download the presentation, then operation proceeds to step 816, and the packaged assets maintained  
 30 by host 500 (e.g., in the form of a self-executing file) are transferred to the recipient's machine. In one embodiment, the presentations may be designated by the subscriber as downloadable or as not downloadable. The subscriber may make this designation

5 when transmitting a presentation to host 500, or at some later time.

On the other hand, if the recipient wishes to have host 500 stream the presentation in real time, then operation proceeds to step 818, and server 504 coordinates the presentation, by  
10 transmitting appropriate instructions to the media server(s) 508 and web server 505. Playback of a presentation is described in detail above in connection with FIGS. 6 and 7. In this embodiment, the presentation is streamed to the recipient over the Internet 514 in a conventional manner.

15 Referring now to FIGS. 18 through 21, there are shown illustrative embodiments of suitable screen shots that are generated by host 504 and presented at client 512. FIG. 18 shows a suitable log-in screen, that includes plural interface elements 505, 507, and 509, into which log-in data may be entered by a user  
20 at client 512. User information, for example an e-mail address, is entered into element 505, and a corresponding password or other information is entered into element 507. Element 509 may be selected by a user such that host 500 will recognize the user each time the user accesses host 500 from a particular machine. The  
25 log-in screen also includes "Log In" and "Reset" screen elements 511 and 513 that may be selected by a user. In addition, a new user may select a "Sign Up" element 515 to register with host 500.

FIG. 19 shows a user account information screen that presents account information to a registered user. In one embodiment, the  
30 presentation of account information and interaction with a user is performed by interface server 504. The account information is preferably presented to the user in the form of a presentation manager table 613, with each row in the table corresponding to a

5 particular presentation. Table 613 provides a password window 615 into which the user may enter or change a password.

Table 613 also includes "Delete" elements 617 that may be selected to delete one or more of the presentations from host 500. If one or more of the Delete elements are selected, server 504  
10 accesses SQL server 506, determines the locations of the corresponding directories for that presentation, and then deletes those directories from the respective servers of host 500. Thus, by maintaining the associations in SQL server 506, deleting a presentation is a relatively straightforward procedure.

Table 613 also provides Download icons 619 and "Send URL" icons 621 to, respectively, download a presentation, and generate an e-mail message that is sent to one or more recipients, as is described above. The account information screen also includes an "Update Passwords" icon 623 and a "Delete Selected" icon 625, which  
15 can be selected to carry out the respective functions based on information entered into table 613 by a user.

FIG. 20 shows a screen presented to a user at client 512 when the user selects "Send URL" icon 621 in the account screen shown in FIG. 19. The screen in FIG. 20 includes an element 701 into which  
20 the desired recipient or recipients' e-mail addresses are entered, as well as an element 703 into which a message may be entered (e.g., the message may include the password that is used to restrict access to the presentation). The screen also includes Send and Cancel elements 705 and 707. Clicking on the Send element  
25 705 causes server 504 to generate an e-mail message and to forward the data on to mail server 510, which then transmits the e-mail to the one or more recipients.

5           FIG. 21 shows a recipient interface screen presented to a  
recipient that has used the URL in a received e-mail message to  
access host 500. The interface screen includes an element 801 into  
which a password may be entered, such as a password included in the  
e-mail message received by the recipient. The interface screen  
10 also includes a "View Presentation" element 803 that can be  
selected by a recipient to have the presentation presented to them  
by host 500, as described above. In addition, the interface screen  
also includes a "Download" element 805 that can be selected by a  
recipient to receive a copy of the packaged presentation from host  
15 500, again as described above.

While the various servers 504, 505, 506, 508, and 510 are  
depicted and described as being embodied as separate servers, it  
will be apparent to those skilled in the art that two or more of  
the servers can be combined into a single server that performs  
multiple functions. In addition, while in the illustrative  
20 embodiment the interface/web server 504 interfaces with clients  
512, unpackages the incoming packaged presentations, and also  
manages the web-based files, it will be apparent that those  
functions can be performed by separate servers. Thus, host 500 may  
25 include a single server that performs all of the above-described  
function, or alternatively, the various functions can be split  
between two or more servers.

While the above description has focused primarily on a  
presentation consisting of screen slides and corresponding audio,  
30 it will be readily understood by those having ordinary skill in the  
art that the various aspects of the present invention, including  
host 500, have utility in connection with other data-presentation  
formats. For example, the present invention may be used to export,

5 package, unpackage, and display presentations consisting of spread  
sheets and corresponding audio clips for one or more of the  
respective cells in the spread sheet, word processing documents  
with corresponding audio clips for the various pages of the  
document, charts, screen capture scenarios, and the like. It will  
10 be understood that the various aspects of the invention, including  
the packaging process, export process, unpackaging process, and  
event handling process, have utility in connection with various  
different types of information, and that the screen slide  
presentation described herein is but one illustrative embodiment of  
15 the utility of the invention. Thus, the export process, packaging  
process, unpackaging process, and event handling process can each  
be used in connection with various types of information. In  
addition, in the case of a presentation consisting of screen slides  
and corresponding audio, the presentation may also include other  
20 information linked and embedded within it. For example, the  
presentation may include a table of contents that is used for  
navigating within the presentation. In addition, the presentation  
may contain bookmarks that can serve as navigation and annotation  
tools.

25 By way of example, in the case of a spreadsheet, the present  
invention may be used to add audio clips (e.g., voice comments) to  
particular cells within the spreadsheet, in a similar manner to the  
audio clips being associated with the respective screen slides.  
The invention will concatenate the audio clips into a file,  
30 compress the file, and assemble the compressed file, spreadsheet  
graphics file, and the other files described above into a single,  
executable file.

5           In addition, a word processing document can be associated with  
 one or more audio clips, wherein the audio clips are linked to  
 particular pages, chapters, paragraphs, and the like, of the  
 document. The export process, packaging process, and unpackaging  
 process are carried out in much the same way as in the case of the  
 10 screen slide presentation.

          As used herein, the term "digital asset" is defined as a  
 collection of data that is presented to a viewer, such as a screen  
 slide, a video clip, an audio clip, a spreadsheet, a word  
 processing document, a web-based file, a streaming media file, and  
 15 the like.

          As used herein, the term "clip" is defined as any of the  
 following: a physical file; a portion of a physical file identified  
 by a pair of start and end points; the concatenation of multiple  
 physical files; the concatenation of multiple segments of one or  
 20 more physical files, where each segment is identified by a pair of  
 points indicating the start and end point for that segment; and the  
 like.

          As used herein, the term "server" is defined as either a  
 computer program run by a computer to perform a certain function,  
 a computer or device on a network that is programmed to perform a  
 specific task (e.g., a database server), or a single computer that  
 is programmed to execute several programs at once, and thereby  
 perform several functions. Thus, the term "server" refers to  
 either a program that is performing a function, or a computer  
 25 dedicated to performing one or more such functions.

          As described above, in the case of a presentation consisting  
 of plural screen slides, the text from each screen slide is  
 preferably extracted and stored in a data file, with such data  
 30

5 being available for searching during subsequent presentation.  
Where the invention is dealing with other types of digital assets,  
some other type of data may be extracted from the respective assets  
for use in intelligently navigating through the presentation. For  
example, in the case of a video signal, closed captioning  
10 information may be extracted from the video and stored in the data  
file. Alternatively, selected video frames may be extracted and  
stored, such as transitory frames or other important frames.  
Moreover, in the case of audio data, key words may be extracted  
from the audio and stored in the data file.

15 In addition, while the above description focuses primarily on  
audio clips being linked to respective digital assets (e.g., screen  
slides, video clips, and the like), the audio clips can be replaced  
with any continuous stream media format, such as video, audio and  
video, animations, telemetry, and the like. Thus, the invention  
20 has utility with any continuous stream media format, and it will be  
understood by those skilled in the art that audio clips are but one  
example thereof.

From the foregoing, it will be apparent to those skilled in  
the art that the system and method of the present invention provide  
25 a central location for managing one or more presentations.

While the above description contains many specific features of  
the invention, these should not be construed as limitations on the  
scope of the invention, but rather as exemplary embodiments  
thereof. Many other variations are possible. Accordingly, the  
30 scope of the invention should be determined not by the embodiments  
illustrated, but by the appended claims and their legal  
equivalents.